

										
Number of legs	1	2	1	2	2	2	3-4	3-4		
Load Direction	0°	0°	90°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.
Thread	WLL tonnes									
M8	0.30	0.60	0.30	0.60	0.42	0.30	0.30	0.63	0.45	0.30
M10	0.63	1.26	0.63	1.26	0.88	0.63	0.63	1.32	0.95	0.63
M12	1.00	2.00	1.00	2.00	1.40	1.00	1.00	2.10	1.50	1.00
M14	1.20	2.40	1.20	2.40	1.70	1.20	1.20	2.50	1.80	1.20
M16	1.50	3.00	1.50	3.00	2.10	1.50	1.50	3.10	2.20	1.50
M18	2.00	4.00	2.00	4.00	2.80	2.00	2.00	4.20	3.00	2.00
M20	2.50	5.00	2.50	5.00	3.50	2.50	2.50	5.20	3.70	2.50
M24	4.00	8.00	4.00	8.00	5.60	4.00	4.00	8.40	6.00	4.00
M27	4.00	8.00	4.00	8.00	5.60	4.00	4.00	8.40	6.00	4.00
M30	5.00	10.00	5.00	10.00	7.00	5.00	5.00	10.50	7.50	5.00
M36	7.00	14.00	7.00	14.00	9.80	7.00	7.00	14.70	10.50	7.00
M36	8.00	16.00	8.00	16.00	11.20	8.00	8.00	16.80	12.00	8.00
M42	10.00	20.00	10.00	20.00	14.00	10.00	10.00	21.00	15.00	10.00
M42	15.00	30.00	15.00	30.00	21.00	15.00	15.00	31.50	22.50	15.00
M48	20.00	40.00	20.00	40.00	28.00	20.00	20.00	42.00	30.00	20.00